skyfloor

SKYFLOOR BL


TECHNICAL DATA

THE WALK-ON LIGHT SHAFT GLAZING

FORM

Choose the form of the walk-on light shaft glazing with integrated ventilation grid that best meets your needs. Built as standard, with a customised finish. Wide variety of add-ons can be individualised.









CONSTRUCTION

- 1 1 static laminated safety glass *
- 2 stainless steel frame brushed with integrated ventilation grid
- 3 steel core for glass support
- 4 sealing joint black
- 5 ceramic strips black (optional)



DIMENSIONS



STANDARD RECTANGLE SIZES:



Weight: approx. 80 kg per m²

INDIVIDUAL SIZES AT THE PRICE OF THE INDICATED STANDARD SIZES.


^{*}laminated safety glass glazed in factory-provided frame

CONNECTION


After removal of the metal grate, the installation of the Skywell BI walk-on light shaft cover can be undertaken by the client, or by a local specialist.

For outdoor installations we recommend a 2% incline to ensure drainage of rain and condensate.

WALL CONNECTION



CONNECTION OPTIONS



GLASS

Choose the glazing that best meets your needs.

	uninsulated
luminous transmission index tL (in%)	continually walkable 83
carrying capacity (kN/m2)	5

In standard sizes, the Skyfloor BL provides a complete ready-to-install glass frame system comprising a vented frame with integrated walk-on glazing.

The given values are for guidance purposes

STANDARD

Skyfloor BL meets the standards for walk-on glazing required in Germany, Austria and Switzerland.